

mod. **PKS 1200**

self-propelled movement at a maximum height of 12 m.  
Approved for outdoor use with 2 operators and max capacity of 200 kg.



PKS 1200  
PLATFORM WITH A  
COMPETITIVE PRICE,  
MAXIMUM HEIGHT AND  
REDUCED WEIGHT.

# PKS 1200

Max capacity		200 kg
Number of people		2
Use		External
<b>A</b>	Closed machine height	2450 mm
<b>B</b>	Minimum platform height	600 mm*
<b>C</b>	Maximum platform height	10200 mm
<b>D</b>	Base overall dimensions	1920 mm
<b>E1</b>		2150 mm
<b>E2</b>		2785 mm
<b>F</b>		980 mm
<b>G</b>	Cage dimensions	980 mm
<b>H1</b>		1200 mm
<b>H2</b>		1835 mm
Machine weight		2180 kg**
Power supply		24 V
Batteries		N° 2 12V Acid Batteries 130Ah
Battery charger		110V – 230V 50/60HZ
Climbing ability at height		1°-1,7%
<b>I</b>	Maximum climbing ability	15%
Drive wheels dimension		Ø 240 x 100
Swivel wheels dimensions (fixed)		Ø 250 x 100
Turning radius		1990 mm
Max. speed (rising)		0,3 m/s
Max. speed (descending)		0,2 m/s
Maximum shifting speed		1,25 m/s
Maximum shifting speed at height		0,12 m/s
<b>C1</b>	Max. height of self-movement at a height with the extensible basket closed	6000 mm
<b>J</b>	Maximum pressure for wheel at full load	8,4 kN***

\* There is an intermediate step.

\*\* Inclusive of extensible picker

\*\*\* Maximum pressure whereas the weight of the platform plus the maximum load on the basket are completely distributed on one side of the platform (totally asymmetric load).

