

ELEVAH® 65TB

Max. working height		6,5 m
Max capacity		120 kg
Number of people		1
Use		Internal
A	Closed machine height	1720 mm
B	Minimum platform height*	600 mm
C1	Maximum platform height for basket rotation	3800 mm
C2	Maximum platform height with closed basket	4500 mm
D	Base overall dimensions	780 mm
E		1280 mm
F		1480 mm
G	Cage dimensions	830 mm
H		700 mm
I		1300 mm
J	Storage tray	440 mm
K		740 mm
Capacity of storage tray		20 kg
Machine weight		1055 kg
Drive wheels dimension		Ø 220 x 65 mm
Swivel wheels dimensions		Ø 200 x 50 mm
Power supply		24 V
Batteries		Lead-Acid Batteries 12V 105 Ah
Battery charger		110V – 230V 50/60HZ
L	Maximum climbing ability	15%
Climbing ability at height		2,5%
Internal turning radius		0
External turning radius		1500 mm
Max. speed (rising – descending)		0,12 m/s - 0,2 m/s
Maximum shifting speed (on the ground - at height)		4 Km/h - 1 Km/h
Self moving up to max. height, with not extended basket		4500 mm
M	Maximum pressure for wheel at full load**	4,1 kN
Work cycles (with fresh batteries) ***		100

* There is an intermediate step.

** Maximum pressure whereas the weight of the platform plus the maximum load on the basket are completely distributed on one side of the platform (totally asymmetric load).

*** By work cycle we mean a self-propelled movement of 20 m with a full ascent to and descent from the maximum height and with adjustment of the loading platform.



Compliant with **EN280** rule.
Approved for outdoor use in the absence of wind.

